



ZPMV2.E173108 Wiring, Printed - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

FARADAY PRINTED CIRCUITS LTD

E173108

Pattinson Industrial Estate N

15/17 Faraday Close

Washington, TYNE & WEAR NE38 8QJ UNITED KINGDOM

Type	Cond Width		Cond	SS/ DS/	Max Area Diam	Solder		Max Oper Temp	Flame Class	Meets UL796 DSR	C T I
	Min	Edge				Thk	Diam				
	mm(in)	mm(in)	mic(mil)	DSO	mm(in)	C	sec	C	Class	DSR	I
Multilayer (mass laminated) printed wiring boards.											
MOT	0.125 (0.005)	0.375 (0.015)	16.25 (0.64)	DS	25.4 (1.0)	280	5	105	V-0	All	-
MOT1	0.125 (0.005)	0.125 (0.005)	16.25 (0.64)	DS	127 (5.0)	260	5	130	V-0	All	-
Multilayer printed wiring boards.											
M1	0.08 (0.003)	0.08 (0.003)	18 (0.71) Int:70	DS	25.4 (1.0)	265	5	130	V-0	All	*
M2	0.08 (0.003)	0.08 (0.003)	18 (0.71) Int:70	DS	127 (5.0)	265	5	120	V-0	All	*
Single layer metal based printed wiring boards.											
IMS-1	0.080 (0.003)	0.080 (0.003)	35 (1.38)	SS	127.0 (5.0)	280	5	90	V-0	All	0
Single layer printed wiring boards.											
P	0.08 (0.003)	0.08 (0.003)	16.5 (0.65)	DS	25.4 (1.0)	280	5	105	V-0	All	*
P2	0.08 (0.003)	0.08 (0.003)	16.25 (0.64)	DS	127 (5.0)	260	5	130	V-0	All	*

* - CTI PLC is marked on individual board.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2015-01-22

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC